

Features

Light Weight
 UV Resistance
 Fire Resistance
 Impact Resistance

High Plasticity
 Easy Transportability and Installation
 High Degree of Transparency and Thermal Insulation
 10 Years Warranty

Applications

Skylight
 Roofing
 Balcony
 Showroom
 Green House
 Sound Insulation Panel
 Signboard & Billboard
 Bus Stand & Taxi Stand
 Walkway & Overhead Bridge

Specifications

Standard Width : 1220mm & 2100mm
 Standard Length : 12200mm
 Standard Colors : Brown, Blue, Green, Clear, Greenish Blue, Grey, White, Pink, Red, Yellow & Orange.

**Non-standard products (length, width and color) are available subject to a minimum order quantity.*

Characteristics

ITEM	TEST METHOD	UNIT	RESULT
Impact Resistance Izod Impact (Notched) <i>Raw Material - Resin Specification</i> Sheet Curve Radius Limitation Thickness = 6mm > 1050mm Thickness = 10mm > 1750mm	ASTM D 256 Pendulum : 7.5 Joule	J/m	908
Specific Gravity Density, D 23 C	ASTM D 792	Sp gr 23/23°C Kg/m ³	1.2
Flammability Horizontal Burn (Flame Spread)	ASTM D 635	mm/minute	< 25

Sample of the product were tested and found conformed (Test Report No.P05440)

